

*Roll Right  
model*

# *200*

*For Doors up to 14' wide x 14' high*

*Easy installation*

*Easy operation*

*Low maintenance*

*6 standard curtain color choices*

*Motor or chain hoist operation*



*Roll Right warrants model 200 doors to be free of defects in  
craftsmanship and materials for 2 years from date of purchase*

*Roll Right Doors have been manufactured continuously since 1976  
in Marysville, WA*

## **Special Features:**

**Easier installation means lower labor costs.**

**Requires less space overhead and does not hinder lighting or overhead storage.**

**Maintenance is minimal and generally is performed by applying light oil to springs, bushings and guides.**

**Insulation and perimeter weather brush seal is an option. Insulation is a blanket of reflective double bubble insulation with a bright white interior color glued to inside of curtain. Weather brush is polypropylene strip of filaments mounted in an extruded aluminum retainer which mounts to the door jamb and conforms to the corrugated surface of the door.**

**Model 200 doors can be motor operated, chain hoist operated or push up operation.**

## **Specifications:**

**Door curtain is assembled of cold roll formed 26-gauge high grade galvanized steel panels coated with baked on polyester paint. Panels are assembled and lock seamed to form a solid steel curtain.**

**Roller drum is a 1.25" schedule 40 pipe with steel drums welded. Helical wound springs are factory installed to properly counter balance the weight of the door curtain**

**Bottom edge is made of extruded aluminum and includes a blade style gasket seal.**

**Guides are made of extruded aluminum and has a vinyl wear strip to buffer door curtain movement.**

**Support brackets are constructed of 12-gauge galvanized steel with heavy bushings to carry the roller drum**

**Lock options: outside mounted pad lock hasp or inside box lock.**

## **Clearances:**

**Side room required: 7.5" for push up operation, 11.5" reduced drive chain hoist operation and 20" for electric motor operation**

**Head room required: 19" up to 10' high 22" up to 14' high**

## *Model 200 list prices*

14" H	1160	1290	1420	1565	1710	1770	1815
13' H	1040	1160	1280	1425	1570	1620	1665
12' H	920	1030	1140	1285	1430	1470	1510
11' H	910	1000	1095	1185	1275	1335	1395
10' H	895	970	1045	1085	1120	1200	1275
9' H	880	945	1010	1040	1070	1120	1170
8' H	865	915	960	990	1020	1040	1060
	8' W	9' W	10' W	11' W	12' W	13' W	14' W

## *Options*

*Insulation per square foot \$ 3.00*

*Perimeter weather brush per linear foot \$10*

*Self storage locks \$ 20 each*

*Steel building mounting brackets \$ 80*

*Reduce drive chain hoist \$ 250*

*Linear model J-51 operator \$ 1150*

*Operator or chain hoist drive shaft prep \$ 80*

*Crating for LTL shipment \$ 300*